

SPECIFICATION

SPLIT HORIZONTAL UNITS

MODELS	Cool Only	HOA020C3AB (OD) & HIA020C1AB (ID)	HOA022C3AB (OD) & HIA022C1AB (ID)		
	Heat Pump	HOA020R3AB (OD) & HIA020R1AB (ID)	HOA022R3AB (OD) & HIA022R1AB (ID)		

CABINET					
Construction		Powder coated Gal.Steel	Powder coated Gal.Steel		
Drip Tray		Aluminium	Aluminium		
Weight (kg) HIA / HOA		150 / 230	150 / 230		

COMPRESSOR					
Type		Scroll	Scroll		
No off		1	1		
Starting		DOL (Optional Soft Start)	DOL (Optional Soft Start)		

INDOOR FAN					
Type		Multivane	Multivane		
No Off		1	1		

INDOOR COIL					
Type		Cu Tube / Al (Coated) Fin	Cu Tube / Al (Coated) Fin		
Design Air Flow (l/s)		1000	1100		

OUTDOOR FAN					
Type		Sickle Blade Axial	Sickle Blade Axial		
No Off		1	1		

OUTDOOR COIL					
Type		Cu Tube / Al (Coated) Fin	Cu Tube / Al (Coated) Fin		

REFRIGERATION					
Refrigerant		R410A	R410A		
Control(s)		TXV	TXV		
Charge (kg)		-	-		
Filter/Drier		Std	Std		
Accumulator		Std	Std		
HP/LP		Non Adjustable Auto Reset	Non Adjustable Auto Reset		

ELECTRICAL					
Supply Volts/Phase/Freq		415 / 3 / 50	415 / 3 / 50		
Indoor fan FLA/LRA/No of Ph.		9.1 / / 1 (240 VAC)	9.1 / / 1 (240 VAC)		
Compressor FLA/LRA/No of Ph.		14.5 / 87.0 / 3	17.0 / 100.0 / 3		
System FLA (incl. ID fan)		23.6	26.1		
System RLA @ ARI (incl. ID fan)		19.9	22.4		

AIR FILTERS					
Fitted		OPTION	OPTION		
No off		-	-		
Dimensions		-	-		

SOUND					
SPL@3M(dB(A))		52	52		
SWL (dB(A))		69	69		