

SPECIFICATION

SPLIT HORIZONTAL UNITS

MODELS	Cool Only	HOA055C3AD (OD) & HIA055C3AD (ID)	HOA065C3AD (OD) & HIA065C3AD (ID)		
	Heat Pump	HOA055R3AD (OD) & HIA055R3AD (ID)	HOA065R3AD (OD) & HIA065R3AD (ID)		

CABINET					
Construction		Powder Coated Galvanized Steel	Powder Coated Galvanized Steel		
Drip Tray		Aluminium	Aluminium		
Weight (kg) HIA / HOC		660 / 500	660 / 500		

COMPRESSOR					
Type		Scroll	Scroll		
No off		2	2		
Starting		DOL (Optional Soft Start)	DOL (Optional Soft Start)		

INDOOR FAN					
Type		EC Plug	EC Plug		
No Off		2	2		

INDOOR COIL					
Type		Cu Tube / Al (Coated) Fin	Cu Tube / Al (Coated) Fin		
Design Air Flow (L/s)		2750	3250		

OUTDOOR FAN					
Type		Sickle Blade Axial	Sickle Blade Axial		
No Off		2	2		

OUTDOOR COIL					
Type		Cu Tube / Al (Coated) Fin	Cu Tube / Al (Coated) Fin		

REFRIGERATION					
Refrigerant		R410A	R410A		
Control(s)		TXV	TXV		
Charge (kg)		-	-		
Filter/Drier		Std	Std		
Accumulator		Std	Std		
HP/LP		Non Adjustable Auto Reset	Non Adjustable Auto Reset		

ELECTRICAL					
Supply Volts/Phase/Freq		400 / 3 / 50	400 / 3 / 50		
ID fan each FLA/LRA/No of Ph.		5.0 / --- / 3	5.0 / --- / 3		
Compressor FLA/LRA/No of Ph.		17.4 / 110.0 / 3	19.6 / 125.0 / 3		
System FLA (incl. ID fan)		44.6	49.0		
System RLA @ ARI (incl. ID fan)		36.5	45.6		

AIR FILTERS					
Fitted		OPTION	OPTION		
No off		-	-		
Dimensions		-	-		

SOUND					
SPL@3M(dB(A))		61	61		
SWL (dB(A))		78	78		