

SPECIFICATION

SPLIT HORIZONTAL UNITS



MODELS	Cool Only	HOA012C3AC (OD) & VIA012C1AA (ID)	HOA015C3AC (OD) & VIA015C1AA (ID)	HOA017C3AC (OD) & VIA017C1AA (ID)	
	Heat Pump	HOA012R3AC (OD) & VIA012R1AA (ID)	HOA015R3AC (OD) & VIA015R1AA (ID)	HOA017R3AC (OD) & VIA017R1AA (ID)	

CABINET				
Construction	Powder coated Gal.Steel	Powder coated Gal.Steel	Powder coated Gal.Steel	
Drip Tray	Aluminium	Aluminium	Aluminium	
Weight (kg) VIA / HOA	340 / 175	340 / 180	340 / 180	

COMPRESSOR				
Type	Scroll	Scroll	Scroll	
No off	1	1	1	
Starting	DOL (Optional Soft Start)	DOL (Optional Soft Start)	DOL (Optional Soft Start)	

INDOOR FAN				
Type	Multivane	Multivane	Multivane	
No Off	1	1	1	

INDOOR COIL				
Type	Cu Tube / Al (Coated) Fin	Cu Tube / Al (Coated) Fin	Cu Tube / Al (Coated) Fin	
Design Air Flow (l/s)	600	750	900	

OUTDOOR FAN				
Type	Sickle Blade Axial	Sickle Blade Axial	Sickle Blade Axial	
No Off	1	1	1	

OUTDOOR COIL				
Type	Cu Tube / Al (Coated) Fin	Cu Tube / Al (Coated) Fin	Cu Tube / Al (Coated) Fin	

REFRIGERATION				
Refrigerant	R410A	R410A	R410A	
Control(s)	TXV	TXV	TXV	
Charge (kg)	-	-	-	
Filter/Drier	Std	Std	Std	
Accumulator	Std	Std	Std	
HP/LP	Non Adjustable Auto Reset	Non Adjustable Auto Reset	Non Adjustable Auto Reset	

ELECTRICAL				
Supply Volts/Phase/Freq	415 / 3 / 50	415 / 3 / 50	415 / 3 / 50	
Indoor fan FLA/LRA/No of Ph.	6.8 / / 1 (240 VAC)	6.8 / / 1 (240 VAC)	6.8 / / 1 (240 VAC)	
Compressor FLA/LRA/No of Ph.	10.0 / 60.0 / 3	11.5 / 70.0 / 3	11.9 / 82.0 / 3	
System FLA (incl. ID fan)	18.3	19.8	20.2	
System RLA @ ARI (incl. ID fan)	14.0	16.1	17.5	

AIR FILTERS				
Fitted	OPTION	OPTION	OPTION	
No off	-	-	-	
Dimensions	-	-	-	

SOUND				
SPL@3M(dB(A))	52	52	56	
SWL (dB(A))	69	69	73	